

[2017-08-15 Lead2pass 300-175 Exam Questions Free Download (196-220)]

2017 August Cisco Official New Released 300-175 Dumps in Lead2pass.com! 100% Free Download! 100% Pass Guaranteed! I'm currently studying for Cisco exam 300-175 I do enjoy studying for exams. It's hard, but it's an excellent forcing function. I learn bits and pieces here and there now and then about this and that, but when I have an exam schedule for a set date, I have to study! And not only do I put in more hours, but I follow a more systematic approach. In this article, I'm going to share Lead2pass braindumps in case you too are studying and this method works for you. Following questions and answers are all new published by Cisco Official Exam Center: <https://www.lead2pass.com/300-175.html>

QUESTION 196 You plan to configure a SAN boot from the iSCSI storage of a Cisco UCS system. Which statement about an iSCSI vNIC is true? A. All iSCSI data traffic is carried over the vNIC after the boot. B. An iSCSI vNIC is an iBFT configuration placeholder for the iSCSI boot configuration. The vNIC exists only during the startup phase. C. Only iSCSI control data traffic is carried over the vNIC after the boot. D. An iSCSI vNIC is an iBFT configuration placeholder for the iSCSI boot process. The vNIC exists during and after the startup phase. Answer: A

QUESTION 197 Which two statements are true concerning authorization when using RBAC in a Cisco Unified Computing System? (Choose two.) A. A locale without any organizations, allows unrestricted access to system resources in all organizations. B. When a user has both local and remote accounts, the roles defined in the remote user account override those in the local user account. C. A role contains a set of privileges which define the operations that a user is allowed to take. D. Customized roles can be configured on and downloaded from remote AAA servers. E. The logical resources, pools and policies, are grouped into roles. Answer: CE

QUESTION 198 Which actions must be taken in order to connect a NetApp FCoE storage system to a Cisco UCS system? A. Ensure that the Fibre Channel switching mode is set to Switching, and use the Fibre Channel ports on the Fabric Interconnects. B. Ensure that the Fibre Channel switching mode is set to Switching, and reconfigure the port to a FCoE Storage port. C. Ensure that the Fibre Channel switching mode is set to End-Host, and use the Ethernet ports on the Fabric interconnects. D. Ensure that the Fibre Channel switching mode is set to Switching, and use the Ethernet ports on the Fabric Interconnects. Answer: A

QUESTION 199 Which two protocols are accepted by the Cisco UCS Manager XML API? (Choose two.) A. SMASHB. HTTPSC. HTTPD. XMTPE. SNMP Answer: AE

QUESTION 200 An Cisco UCS Administrator is planning to complete a firmware upgrade using Auto install. Which two options are prerequisites to run Auto Install? (Choose two.) A. minor fault fixingB. configuration backupC. service profiles unmounted from the blade serversD. time synchronizationE. fault suppression started on the blade servers Answer: AB

QUESTION 201 Which two prerequisites are required to configure a SAN boot from the FCoE storage of a Cisco UCS system? (Choose two.) A. The Cisco UCS domain must be able to communicate with the SAN storage device that hosts the operating system image. B. A boot policy must be created that contains a local disk, and the LVM must be configured correctly. C. There must be iVR-enabled FCoE proxying between the Cisco UCS domain and the SAN storage device that hosts the operating system image. D. There must be a boot target LUN on the device where the operating system image is located. E. There must be a boot target RAID on the device where the operating system image is located. Answer: CD

QUESTION 202 You need to configure service profiles for a Cisco UCS system. What is an advantage of using the Export wizard to create the service profiles instead of using the Simple wizard? A. Only the Expert wizard supports Fabric Interconnect expansion module ports to be used in 10-Gigabit uplink mode or Fibre Channel mode. B. Both wizards support the same features, but the Expert wizard provides no configuration options for the features. C. The Expert wizard supports stateless computing and mobile service profiles. D. The Expert wizard supports all blade generations, whereas the Simple wizard supports only M1 blades, M2 blades, and Cisco VIC cards. Answer: B

QUESTION 203 You have a Cisco UCS system. You need to create VSAN 100 on a Cisco Nexus Series switch and to enable switch port fc 1/10 as a member for the VLAN. Which command set should you use? A. SITE-A-MDS-Fabric-A# vsan databaseSITE-A-MDS-Fabric-A (vsan-db)# vsan 100 interface fc 1/10SITE-A-MDS-Fabric-A (vsan-db)# vsan database commitSITE-A-MDS-Fabric-A (vsan-db)# exitB. SITE-A-MDS-Fabric-A# configure terminalSITE-A-MDS-Fabric-A (config)# vsan databaseSITE-A-MDS-Fabric-A (config-vsan-db)# vsan 100 interface fc 1/10SITE-A-MDS-Fabric-A (config-vsan-db)# exitC. SITE-A-MDS-Fabric-A# configure terminalSITE-A-MDS-Fabric-A (config)# vsan databaseSITE-A-MDS-Fabric-A (config-vsan-db)# vsan 100 interface fc 1/10SITE-A-MDS-Fabric-A (config-vsan-db)# vsan database commitSITE-A-MDS-Fabric-A (config-vsan-db)# vsan database commitD. SITE-A-MDS-Fabric-A# configure terminalSITE-A-MDS-Fabric-A (config)# vsan databaseSITE-A-MDS-Fabric-A (config-vsan-db)# vsan 100 interface fc 1/10SITE-A-MDS-Fabric-A (config-vsan-db)# vsan database commitSITE-A-MDS-Fabric-A (config-vsan-db)# exit Answer: C

QUESTION 204 You need to implement a Cisco UCS system at a customer site. Which adapters and operating systems have preprovisioned adapter policies? A. Ethernet vNICs and Windows. OS X Server, and Oracle Solaris operating systemsB. Fibre Channel vNICs and Windows, FreeBSD, and Linux operating systemsC. Ethernet vNICs and Windows, VMware, and Linux operating systemsD. Fibre Channel vNICs and Windows, Oracle Solaris, and

Linux operating systems Answer: D QUESTION 205 You need to automate the management of servers, networks, and storage on a Cisco UCS system, by using PowerShell. Which tool should you use? A. Cisco UCS Platform Emulator B. Cisco UCS Python SDK C. Cisco UCS Automation Tool D. Cisco UCS PowerTool Suite Answer: D Explanation:

http://www.cisco.com/c/en/us/solutions/collateral/data-center-virtualization/microsoft-applications-on-ucs/brochure_c02-705764.html QUESTION 206 Which two Cisco UCS firmwares are contained in the Cisco UCS Infrastructure software bundle? (Choose two.)

A. Cisco I/O module firmware B. Cisco IMCC C. Cisco UCS BIOS D. Cisco UCS fabric interconnects firmware E. Cisco UCS adapters Answer: BD QUESTION 207 A server discovery policy is defined in Cisco UCS Manager. Which two actions are initiated by the policy when a new server starts? A. The qualification in the server discovery policy is executed against the server. B. The scrub policy is applied to the server, if configured. C. A service profile is created for the server with the identity burned into the server at time of manufacture. D. The inventory of the server is analyzed. E. The server is assigned to the selected organization, if configured. Answer: BE QUESTION 208 Refer to the exhibit. Which type of FCoE topology is displayed? A. direct-attach B. remote-attach C. vPC D. FCoE with Cisco 2232 Fabric Extenders Answer: A QUESTION 209 Which two statements about the service profile configuration options in the Cisco UCS Manager GUI are true? (Choose two.) A. It can be generated automatically from the service profile template. B. It can be derived from the chassis discovery policy. C. It can be derived from the initial template or the updating template. D. It can be configured by cloning a virtual machine profile. E. It can be configured by using the chassis connectivity policy. Answer: BE QUESTION 210 Which consideration must be made while performing backup operations within the Cisco UCS Manager? A. Each backup destination can have multiple backup operations. B. Backups can be scheduled ahead of time. C. A user can perform incremental backups of a system configuration. D. Rerunning an existing backup operation overwrites the existing backup file. Answer: D QUESTION 211 You need to identify which DCB standard provides those functionalities: negotiation capabilities for features, the distribution of parameters from one node to another, and logical link up and down signaling for both Ethernet and fibre Channel interfaces. Which DCB standard should you identify? A. ETSB B. PFCC C. DCBX D. QCN Answer: B QUESTION 212 Which two protocols does the Cisco Integrated Management Controller support for managing standalone Cisco UCS C-Series servers? (Choose two.) A. SMASH CLPB. IPMIv2 C. SoL D. SNMPv3 E. Virtual KVM Answer: BD Explanation:

http://www.cisco.com/c/en/us/products/collateral/servers-unified-computing/ucs-manager/whitepaper_c11-701809.html QUESTION 213 You are configuring service profiles for a Cisco UCS system. What are three types of logical resource pools? (Choose three.) A. UUID B. MAC C. VLAN D. WWN E. VXLAN F. FC Answer: ABD QUESTION 214 In order to manually boot from the FlexFlash SD card, which boot option must be in the boot policy used in the service profile? A. FlexFlash state B. remote virtual drive C. remote boot D. SD card Answer: A QUESTION 215 Which two items represent the features of Call Home on the Cisco Unified Computing System? (Choose two.) A. syslog B. send fault details to Cisco TACC C. SNMP trap receiver D. send email alerts to administrators E. central repository of normalized fault data Answer: BD QUESTION 216 In an environment where multiple LDAP servers are used for user authentication, which Cisco UCS Manager feature must be configured? A. LDAP Locale B. Organization C. LDAP Provider Group D. Authentication Domain Answer: C QUESTION 217 You need to upgrade the firmware on 15 Cisco UCS C-Series Rack Servers. Ten of the servers are integrated in a Cisco UCS cluster, and the other five servers are used in standalone mode. The Cisco UCS C-Series Rack-Mount Server Software Bundle is available. Which set of statements about the upgrade process is true? A. You cannot upgrade the firmware on the servers in standalone mode. You must cluster the servers first over LAN or via cluster interfaces. After the firmware upgrade, you can revert the five servers to standalone mode. B. You cannot use the Cisco UCS C-Series Rack-Mount Server Software Bundle with Cisco UCS C-Series Servers in standalone mode. You must download and use the Cisco UCS C-Series Rack-Mount Standalone Server Software package. C. First, you must integrate the standalone servers into the Cisco UCS system. Then, you can upgrade the firmware on all 15 servers from Cisco UCS Manager. Finally, you can revert the five servers to standalone mode. D. You can upgrade the firmware on all of the Cisco UCS C-Series Rack Servers by using the Cisco UCS C-Series Rack-Mount Standalone Server Software. You can upgrade the 10 servers that are integrated in a Cisco UCS cluster in Cisco UCS Manager, and you can upgrade the five standalone servers one by one. Answer: D QUESTION 218 Which two features in Cisco UCS Manager are required to configure Uplink Ethernet ports? (Choose two.) A. vNIC templates B. LAN Pin Groups C. VLAN Groups D. adapter policies E. link profiles Answer: BC QUESTION 219 You need to enable Cisco UCS Manager to support out-of-band IPv4 address access to the Cisco UCS KVM Direct launch page from a web browser. What should you enable? A. SMASH CLPB. CIM XML C. SNMP D. CIMC Web Service Answer: B Explanation:

http://www.cisco.com/c/en/us/td/docs/unified_computing/ucs/ucs-manager/GUI-User-Guides/Admin-Management/3-1/b_Cisco_UCS_Admin_Mgmt_Guide_3_1/b_Cisco_UCS_Admin_Mgmt_Guide_3_1_chapter_0110.html QUESTION 220 After an admin

configures a service profile template and associates it to the blade, the admin notices that changes to the template are not automatically pushed to profiles that are inheriting that template. The service profile template and vNIC templates are set to "initial". Which two actions resolve this issue? (Choose two.) A. Delete the service profile template and re-create it as an updating template. B. Change the type of the service profile template from "initial" to "updating". C. Delete the vNIC template and re-create it as an updating template. D. Change the type of the vNIC template from "initial" to "updating". E. Delete and recreate all templates.

Answer: AD If you want to prepare for 300-175 exam in shortest time, with minimum effort but for most effective result, you can use Lead2pass 300-175 dump which simulates the actual testing environment and allows you to focus on various sections of 300-175 exam. Best of luck! 300-175 new questions on Google Drive:

<https://drive.google.com/open?id=0B3Syig5i8gpDODBCSGdMUUFFc1U> 2017 Cisco 300-175 exam dumps (All 255 Q&As) from Lead2pass: <https://www.lead2pass.com/300-175.html> [100% Exam Pass Guaranteed]