

[2017 New 200-105 New Questions For Passing The 200-105 Certification Exam (101-125)]

2017 June Cisco Official New Released 200-105 Dumps in Lead2pass.com! 100% Free Download! 100% Pass Guaranteed! Test your preparation for Cisco 200-105 with these actual 200-105 new questions below. Exam questions are a sure method to validate one's preparation for actual certification exam. Following questions and answers are all new published by Cisco Official Exam Center: <http://www.lead2pass.com/200-105.html>

QUESTION 101 Which command displays the CHAP authentication process as it occurs between two routers? A. debug chap authentication B. debug authentication C. debug chap ppp D. debug ppp authentication
Answer: D

QUESTION 102 A department decides to replace its hub with a Catalyst 2950 switch that is no longer needed by another department. To prepare the switch for installation, the network administrator has erased the startup configuration and reloaded the switch. However, PCs that are connected to the switch experience various connectivity problems. What is a possible cause of the problem? A. The VLAN database was not erased. B. The management VLAN is disabled. C. The running configuration should have been erased. D. The "mode" button was not pressed when the switch was reloaded. E. The switch was not configured with an IP address or a default gateway.
Answer: A

QUESTION 103 Refer to the exhibit. The following commands are executed on interface fa0/1 of 2950 Switch. 2950Switch(config-if)# switchport port-security 2950Switch(config-if)# switchport port-security mac-address sticky 2950Switch(config-if)# switchport port-security maximum 1 The Ethernet frame that is shown arrives on interface fa0/1. What two functions will occur when this frame is received by 2950Switch? (Choose two.) A. The MAC address table will now have an additional entry of fa0/1 FFFF.FFFF.FFFF. B. Only host A will be allowed to transmit frames on fa0/1. C. This frame will be discarded when it is received by 2950Switch. D. All frames arriving on 2950Switch with a destination of 0000.00aa.aaaa will be forwarded out fa0/1. E. Hosts B and C may forward frames out fa0/1 but frames arriving from other switches will not be forwarded out fa0/1. F. Only frames from source 0000.00bb.bbbb, the first learned MAC address of 2950Switch, will be forwarded out fa0/1.
Answer: B
Explanation: The first command 2950Switch(config-if)# switchport port-security is to enable the port-security in a switch port. In the second command 2950Switch(config-if)# switchport port-security mac-address sticky, we need to know the full syntax of this command is switchport port-security mac-address sticky [MAC]. The STICKY keyword is used to make the MAC address appear in the running configuration and you can save it for later use. If you do not specify any MAC addresses after the STICKY keyword, the switch will dynamically learn the attached MAC Address and place it into your running-configuration. In this case, the switch will dynamically learn the MAC address 0000.00aa.aaaa of host A and add this MAC address to the running configuration. In the last command 2950Switch(config-if)# switchport port-security maximum 1 you limited the number of secure MAC addresses to one and dynamically assigned it (because no MAC address is mentioned, the switch will get the MAC address of the attached MAC address to interface fa0/1), the workstation attached to that port is assured the full bandwidth of the port. Therefore only host A will be allowed to transmit frames on fa0/1 -> B is correct. After you have set the maximum number of secure MAC addresses for interface fa0/1, the secure addresses are included in the "Secure MAC Address" table (this table is similar to the Mac Address Table but you can only view it with the show port-security address command). So in this question, although you don't see the MAC address of host A listed in the MAC Address Table but frames with a destination of 0000.00aa.aaaa will be forwarded out of fa0/1 interface -> D is correct.

QUESTION 104 Which two statements describe characteristics of IPv6 unicast addressing? (Choose two.) A. Global addresses start with 2000::/3. B. Link-local addresses start with FE00::/12. C. Link-local addresses start with FF00::/10. D. There is only one loopback address and it is ::1. E. If a global address is assigned to an interface, then that is the only allowable address for the interface.
Answer: AD

QUESTION 105 What are three features of the IPv6 protocol? (Choose three.) A. optional IPsec B. autoconfiguration C. no broadcasts D. complicated header E. plug-and-play F. checksums
Answer: BCE

QUESTION 106 A router has two Fast Ethernet interfaces and needs to connect to four VLANs in the local network. How can you accomplish this task, using the fewest physical interfaces and without decreasing network performance? A. Use a hub to connect the four VLANs with a Fast Ethernet interface on the router. B. Add a second router to handle the VLAN traffic. C. Add two more Fast Ethernet interfaces. D. Implement a router-on-a-stick configuration.
Answer: D

QUESTION 107 Refer to the graphic. Users on the Holyoke router are unable to access the intranet server attached to interface E0 of the Chicopee router. Inspection of the routing table of the Holyoke router shows that an entry for the Chicopee E0 network is missing. Which command will configure the Holyoke router with a path to the intranet server network? A. Holyoke(config)# ip host Chicopee 201.73.127.2 B. Holyoke(config)# ip host Chicopee 201.73.127.0 255.255.255.0 C. Holyoke(config)# ip network 202.18.38.0 D. Holyoke(config)# ip network 202.18.18.0 255.255.255.0 E. Holyoke(config)# ip route 202.18.18.0 255.255.255.0 201.73.127.2 F. Holyoke(config)# ip route 201.73.127.2 255.255.255.0 202.18.18.0
Answer: E

QUESTION 108 Refer to the exhibit. What can be determined about the interfaces of the Main_Campus router from the output

shown? A. The LAN interfaces are configured on different subnets. B. Interface FastEthernet 0/0 is configured as a trunk. C. The Layer 2 protocol of interface Serial 0/1 is NOT operational. D. The router is a modular router with five FastEthernet interfaces. E. Interface FastEthernet 0/0 is administratively deactivated. Answer: B

QUESTION 109 Select the action that results from executing these commands. Switch(config-if)# switchport port-security Switch(config-if)# switchport port-security mac-address sticky A. A dynamically learned MAC address is saved in the startup-configuration file. B. A dynamically learned MAC address is saved in the running-configuration file. C. A dynamically learned MAC address is saved in the VLAN database. D. Statically configured MAC addresses are saved in the startup-configuration file if frames from that address are received. E. Statically configured MAC addresses are saved in the running-configuration file if frames from that address are received. Answer: B

QUESTION 110 Which two of these statements are true of IPv6 address representation? (Choose two.) A. There are four types of IPv6 addresses: unicast, multicast, anycast, and broadcast. B. A single interface may be assigned multiple IPv6 addresses of any type. C. Every IPv6 interface contains at least one loopback address. D. The first 64 bits represent the dynamically created interface ID. E. Leading zeros in an IPv6 16 bit hexadecimal field are mandatory. Answer: BC

QUESTION 111 What are two enhancements that OSPFv3 supports over OSPFv2? (Choose two.) A. It requires the use of ARP. B. It can support multiple IPv6 subnets on a single link. C. It supports up to 2 instances of OSPFv3 over a common link. D. It routes over links rather than over networks. Answer: B

Explanation: Here is a list of the differences between OSPFv2 and OSPFv3: They use different address families (OSPFv2 is for IPv4-only, OSPFv3 can be used for IPv6-only or both protocols) OSPFv3 introduces new LSA types OSPFv3 has different packet format OSPFv3 uses different flooding scope bits (U/S2/S1) OSPFv3 adjacencies are formed over link-local IPv6 communications OSPFv3 runs per-link rather than per-subnet OSPFv3 supports multiple instances on a single link, Interfaces can have multiple IPv6 addresses OSPFv3 uses multicast addresses FF02::5 (all OSPF routers), FF02::6 (all OSPF DRs) OSPFv3 Neighbor Authentication done with IPsec (AH) OSPFv2 Router ID (RID) must be manually configured, still a 32-bit number <http://www.networkworld.com/article/2225270/cisco-subnet/ospfv3-for-ipv4-and-ipv6.html>

QUESTION 112 What Netflow component can be applied to an interface to track IPv4 traffic? A. flow monitor B. flow record C. flow sampler D. flow exporter Answer: A

Explanation: A flow monitor is essentially a NetFlow cache. The Flow Monitor has two major components the Flow Record and the Flow Exporter. The flow monitor can track both ingress and egress information. The flow record contains what information being tracked by NetFlow (i.e. IP address, ports, protocol...). The Flow exporter describes the NetFlow export. Flow monitors may be used to track IPv4 traffic, IPv6 traffic, multicast or unicast, MPLS, bridged traffic. Multiple Flow monitors can be created and attached to a specific physical or logical interface. Flow monitors can also include packet sampling information if sampling is required.

http://www.cisco.com/c/en/us/products/collateral/ios-nx-os-software/flexible-netflow/prod_qas0900aecd804be091.html

QUESTION 113 What are three benefits of GLBP? (Choose three.) A. GLBP supports up to eight virtual forwarders per GLBP group. B. GLBP supports clear text and MD5 password authentication between GLBP group members. C. GLBP is an open source standardized protocol that can be used with multiple vendors. D. GLBP supports up to 1024 virtual routers. E. GLBP can load share traffic across a maximum of four routers. F. GLBP elects two AVGs and two standby AVGs for redundancy. Answer: BDE

Explanation: http://www.cisco.com/en/US/docs/ios/12_2s/feature/guide/fs_glb2.html Load Sharing You can configure GLBP in such a way that traffic from LAN clients can be shared by multiple routers, thereby sharing the traffic load more equitably among available routers. Multiple Virtual Routers GLBP supports up to 1024 virtual routers (GLBP groups) on each physical interface of a router, and up to four virtual forwarders per group. Preemption The redundancy scheme of GLBP enables you to preempt an active virtual gateway with a higher priority backup virtual gateway that has become available. Forwarder preemption works in a similar way, except that forwarder preemption uses weighting instead of priority and is enabled by default. Authentication You can use a simple text password authentication scheme between GLBP group members to detect configuration errors. A router within a GLBP group with a different authentication string than other routers will be ignored by other group members.

http://www.cisco.com/en/US/docs/switches/datacenter/sw/5_x/nx-s/unicast/configuration/guide/13_glb.html GLBP Authentication GLBP has three authentication types: MD5 authentication Plain text authentication No authentication MD5 authentication provides greater security than plain text authentication. MD5 authentication allows each GLBP group member to use a secret key to generate a keyed MD5 hash that is part of the outgoing packet. At the receiving end, a keyed hash of an incoming packet is generated. If the hash within the incoming packet does not match the generated hash, the packet is ignored. The key for the MD5 hash can either be given directly in the configuration using a key string or supplied indirectly through a key chain. You can also choose to use a simple password in plain text to authenticate GLBP packets, or choose no authentication for GLBP.

QUESTION 114 What command visualizes the general NetFlow data on the command line? A. show ip flow export B. show ip flow top-talkers C. show ip cache flow D. show mls sampling E. show mls netflow ip Answer: C

Explanation: The following is an example of how to visualize the

information is used to plan, understand new services, and allocate network and application resources (e.g. Web server sizing and VoIP deployment) to responsively meet customer demands. User Monitoring and Profiling--NetFlow data enables network engineers to gain detailed understanding of customer/user utilization of network and application resources. This information may then be utilized to efficiently plan and allocate access, backbone and application resources as well as to detect and resolve potential security and policy violations. Network Planning--NetFlow can be used to capture data over a long period of time producing the opportunity to track and anticipate network growth and plan upgrades to increase the number of routing devices, ports, or higher- bandwidth interfaces. NetFlow services data optimizes network planning including peering, backbone upgrade planning, and routing policy planning. NetFlow helps to minimize the total cost of network operations while maximizing network performance, capacity, and reliability. NetFlow detects unwanted WAN traffic, validates bandwidth and Quality of Service (QOS) and allows the analysis of new network applications. NetFlow will give you valuable information to reduce the cost of operating your network. Security Analysis--NetFlow identifies and classifies DDOS attacks, viruses and worms in real-time. Changes in network behavior indicate anomalies that are clearly demonstrated in NetFlow data. The data is also a valuable forensic tool to understand and replay the history of security incidents. Accounting/Billing--NetFlow data provides fine-grained metering (e.g. flow data includes details such as IP addresses, packet and byte counts, timestamps, type-of-service and application ports, etc.) for highly flexible and detailed resource utilization accounting. Service providers may utilize the information for billing based on time-of-day, bandwidth usage, application usage, quality of service, etc. Enterprise customers may utilize the information for departmental charge-back or cost allocation for resource utilization. NetFlow Data Warehousing and Data Mining--NetFlow data (or derived information) can be warehoused for later retrieval and analysis in support of proactive marketing and customer service programs (e.g. figure out which applications and services are being utilized by internal and external users and target them for improved service, advertising, etc.). In addition, NetFlow data gives Market Researchers access to the "who", "what", "where", and "how long" information relevant to enterprises and service providers.

QUESTION 118 What are the three things that the Netflow uses to consider the traffic to be in a same flow? A. IP address B. Interface name C. Port numbers D. L3 protocol type E. MAC address Answer: ACD

QUESTION 119 Which three are the components of SNMP? (Choose three) A. MIB B. SNMP Manager C. SysLog Server D. SNMP Agent E. Set Answer: ABD

QUESTION 120 What are the Popular destinations for syslog messages to be saved? A. Flash B. The logging buffer .RAM C. The console terminal D. Other terminals E. Syslog server Answer: BCE

QUESTION 121 Syslog was configured with a level 3 trap. Which 3 types of logs would be generated (choose three) A. Emergencies B. Alerts C. Critical D. Errors E. Warnings Answer: ABC

QUESTION 122 Which three statements about Syslog utilization are true? (Choose three.) A. Utilizing Syslog improves network performance. B. The Syslog server automatically notifies the network administrator of network problems. C. A Syslog server provides the storage space necessary to store log files without using router disk space. D. There are more Syslog messages available within Cisco IOS than there are comparable SNMP trap messages. E. Enabling Syslog on a router automatically enables NTP for accurate time stamping. F. A Syslog server helps in aggregation of logs and alerts. Answer: CDE

QUESTION 123 A network administrator enters the following command on a router: logging trap 3. What are three message types that will be sent to the Syslog server? (Choose three.) A. informational B. emergency C. warning D. critical E. debug F. error Answer: BDF

QUESTION 124 What is the default Syslog facility level? A. local4 B. local5 C. local6 D. local7 Answer: D

QUESTION 125 What command instructs the device to timestamp Syslog debug messages in milliseconds? A. service timestamps log datetime localtime B. service timestamps debug datetime msec C. service timestamps debug datetime localtime D. service timestamps log datetime msec Answer: B

These Cisco 200-105 exam questions are all a small selection of questions. If you want to practice more questions for actual 200-105 exam, use the links at the end of this document. Also you can find links for 200-105 VCE software that is great for preparation and self-assessment for Cisco 200-105 exam. **200-105** new questions on Google Drive: <https://drive.google.com/open?id=0B3Syig5i8gpDVzY4ZElvSmlkb2M> 2017 Cisco **200-105** exam dumps (All 402 Q&As) from Lead2pass: <http://www.lead2pass.com/200-105.html> [100% Exam Pass Guaranteed]